DB - DIABLO



SKF Equipped

MODEL	3600	4000	4600	5000
Power required HP	130-240	150-240	170-240	190-240
Power required kW	96-176	110-176	125-176	140-176
Working width mm	3704	4144	4585	5024
Total footprint mm	3751	4191	4631	5071
Tools n°	32	36	40	44
Rotor rpm	345	345	345	345
Weight* W/ CAGE ROLLER Ø510 kg	1880	1990	2150	2350

*Approximate

EQUIPMENT	STANDARD
3 points universal hitch (Category 3N)	●
Front oscillating bar hitch	●
Single speed unit, 1000 rpm	●
Fixed central PTO shaft (tractor side fork 1” 3/8 Z6)	●
Side PTO shaft with shear bolt	●
Rotor spacing 22 cm, with 90×12 mm blades	●
Circular tool carrier shafts – case-hardened – Heavy Duty version	●
Central and side gears – case-hardened – Heavy Duty version	●
Oil-bath transmission housing	●
Automatic hydraulic device with safety transport hooks	●
Hydraulic opening and closing of the units with 2 cylinders and controlled locking valves	●
Height-adjustable side containment guards	●
Pin-adjustable levelling bar for height and distance from the blades	●
Pin-adjustable rear rollers	●
Automatic rear roller alignment device by Valentini – on request	

- For tough or stony soils, it is recommended to fit the harrow with stone protection kit

» Accessories on p. 42 » Rollers on p. 58

Images for illustrative purposes only. The product may vary due to design modifications.