KG - KING



SKF Equipped

MODEL	2500	3000	3500	4000	4500
Power required HP	100-230	120-230	140-230	160-230	180-230
Power required kW	74-169	88-169	103-169	118-169	132-169
Working width mm	2500	3010	3450	3890	4330
Total footprint mm	2550	3077	3517	3957	4397
Tools n°	22	26	30	34	38
Rotor rpm	361	361	361	361	361
Weight* W/ CAGE ROLLER Ø510 kg	1390	1590	1900	2030	2300

*Approximate

EQUIPMENT	STANDARD
3 points universal hitch (Category 3)	●
Front oscillating bar hitch	●
Single speed unit, 1000 rpm	●
Rear PTO	●
Central PTO shaft with shear bolt (tractor side fork 1” 3/8 Z6)	●
Rotor spacing 22 cm, with 100×12 mm blades	●
Circular tool carrier shafts – Heavy Duty version	●
Central and side gears – case-hardened – Heavy Duty version	●
Oil-bath transmission housing	●
Height-adjustable side containment guards	●
Pin-adjustable levelling bar for height and distance from the blades	●
Top link brackets	●
Pin-adjustable rear rollers	●

• For tough or stony soils, it is recommended to fit the harrow with stone protection kit

» Accessories on p. 42 » Rollers on p. 58

Images for illustrative purposes only. The product may vary due to design modifications.