PR - NEW PRINCE

70-120 HP

28 cm



SKF Equipped

MODEL	2250	2500	3000
Power required HP	70-120	80-120	90-120
Power required kW	51-88	59-88	66-88
Working width mm	2350	2500	3010
Total footprint mm	2417	2550	3077
Tools n°	20	22	26
Rotor rpm	360	360	360
Weight* w/ CAGE ROLLER Ø410 kg	850	910	1070

*Approximate

EQUIPMENT	STANDARD
3 points universal hitch (Category 2)	●
Front oscillating bar hitch	●
Single speed unit, 540 rpm	●
Central PTO shaft with shear bolt (tractor side fork 1" 3/8 Z6)	●
Rotor spacing 22 cm, with 90×12 mm blades	●
Circular tool carrier shafts – case-hardened – Heavy Duty version	●
Tool carrier shafts supported by high-performance bearings	●
Central and side gears – case-hardened – Heavy Duty version	●
Oil-bath transmission housing	●
Height-adjustable side containment guards	●
Pin-adjustable levelling bar for height and distance from the blades	●
Mod. 2500/3000: Top link brackets	●
Pin-adjustable rear rollers	●

• For tough or stony soils, it is recommended to fit the harrow with stone protection kit » Accessories on p. 42 » Rollers on p. 58

Images for illustrative purposes only. The product may vary due to design modifications.