

FA-M-S2 - ATTILA-S2



SKF Equipped

HARDOX IN MY BODY

MODEL	1800	2000	2300
Power required HP	350-450	400-450	450-450
Power required kW	261-330	298-330	330-330
Working width mm	1770	1995	2300
Total width mm	2280	2505	2810
Bits* n°	247	269	304
Rotor rpm	190	190	190
Weight** kg	7500	8050	8850

*Net of additional bits for rotor balancing **Approximate

EQUIPMENT	STANDARD
3 points universal hitch (Category 4H N and 4H)	●
Single speed unit, 1000 rpm	●
Ø 1185 reinforced rotor with Ø 35 high-strength, wear-resistant steel bits	●
Protective rings for the transmission support	●
Central PTO shaft with shear bolt (tractor side fork 1” 3/4 Z20)	●
Double side gear transmission in oil bath by Valentini-6G	●
Bearing support with special seals, Labyrinth Bearing Protection by Valentini	●
Rear containment plates and adjustable screening grids for crushed material with hydraulic jacks	●
Front deflectors adjustable by hydraulic jack	●
Counter protective guard in high-strength, wear-resistant steel	●
Friction timing system by Valentini	●

TRACTOR EQUIPMENT REQUIRED
- Variable speed gearbox
- Hydraulic valves: 2–6
- Front ballast if necessary

» Accessories on p. 30

Images for illustrative purposes only. The product may vary due to design modifications.