

FA-N-S2 - ATTILA-S2

STONE CRUSHER



SKF Equipped

HARDOX IN MY BODY

MODEL	1800	2000	2300	2500	2800	3000
Power required HP	220-400	240-400	280-400	320-400	340-400	360-400
Power required kW	162-294	176-294	206-294	235-294	250-294	265-294
Working width mm	1745	1995	2245	2495	2745	2995
Total width mm	2210	2460	2710	2960	3210	3460
Bits* n°	170	185	220	238	256	274
Rotor rpm	258	258	258	258	258	258
Weight** kg	5480	5900	6400	7000	7600	8200

*Al netto dei denti aggiunti per bilanciare il Rotor **Approximate

EQUIPMENT	STANDARD
3 points universal hitch (Category 3 up to mod. 2500, category 3 and 4 from mod. 2800)	●
Single speed unit, 1000 rpm	●
Ø 930 reinforced rotor with Ø 35 high-strength, wear-resistant steel bits	●
Protective rings for the transmission support	●
Central PTO shaft with shear bolt (tractor side fork 1” 3/4 Z20)	●
Double side gear transmission in oil bath by Valentini-4G	●
Bearing support with special seals, Labyrinth Bearing Protection by Valentini	●
Rear containment plates and adjustable screening grids for crushed material with hydraulic jacks	●
Front deflectors adjustable by hydraulic jack	●
Working depth skids adjustable by hydraulic jack	●
Protective shrouds for the side casings	●
Counter protective guard in high-strength, wear-resistant steel	●
Friction timing system by Valentini	●

TRACTOR EQUIPMENT REQUIRED
- Variable speed gearbox
- Hydraulic valves: 2–6
- Front ballast if necessary

» Accessories on p. 30

Images for illustrative purposes only. The product may vary due to design modifications.