

FI - IVAN-S2

STONE CRUSHER



SKF Equipped

HARDOX IN MY BODY

MODEL	1800	2000	2300	2500	2800
Power required HP	180-280	200-280	220-380	230-380	250-380
Power required kW	132-205	147-205	161-279	169-279	183-279
Working width mm	1865	2065	2365	2565	2865
Total width mm	2285	2485	2785	2985	3285
Bits* n°	143	158	185	192	230
Rotor rpm	265	265	265	265	265
Weight** kg	4150	4450	4900	5200	5500

*Net of additional bits for rotor balancing **Approximate

EQUIPMENT	STANDARD
3 points universal hitch (Category 3N, 3 and 4L N)	●
Single speed unit, 1000 rpm	●
Ø 727 reinforced rotor with Ø 35 high-strength, wear-resistant steel bits	●
Protective rings for the transmission support	●
Central PTO shaft with shear bolt (tractor side fork 1” 3/4 Z20)	●
Double side gear transmission in oil bath by Valentini 4G	●
Bearing support with special seals, Labyrinth Bearing Protection by Valentini	●
Rear containment plates and adjustable screening grids for crushed material with hydraulic jacks	●
Adjustable front conveyors with hydraulic jacks	●
Working depth skids adjustable by hydraulic jack	●
Counter protective guard in high-strength, wear-resistant steel	●
Friction timing system by Valentini	●

TRACTOR EQUIPMENT REQUIRED
- Variable speed gearbox
- Hydraulic valves: 2–6
- Front ballast if necessary

» Accessories on p. 30

Immagini fotografiche a scopo illustrativo. Tutte le attrezzature descritte e/o fotografate possono essere dotate di dispositivi non compresi di serie.