MAXI-PREDATOR

STONE CRUSHER

250-350 HP

10-20 cm

15 cm



SKF Equipped

HARDOX IN MY BODY

MODEL	4600
Power required HP	250-350
Power required kW	184-257
Working width mm	4290
Total width mm	4620
Bits* n°	314
Rotor rpm	258
Weight** kg	5340

*Net of additional bits for rotor balancing **Approximate

EQUIPMENT	STANDARD
3 points universal hitch (Category 3)	●
Front oscillating bar hitch	●
Single speed unit, 1000 rpm	●
Size 503 reinforced rotor with Ø 25 high-strength, wear-resistant steel bits	●
Oil-bath idler-side support	●
Protective rings for the transmission support and the idler-side support	●
Fixed central PTO shaft (tractor side fork 1” 3/4 Z20)	●
Side PTO shaft with cam system	●
Hydraulic opening and closing of the units with 4 cylinders and controlled locking valves	●
Side gear transmission in oil bath by Valentini-4G	●
Bearing support with special seals, Labyrinth Bearing Protection by Valentini	●
Rear containment plates and adjustable crushed product screening grids with mechanical jack	●
Counter protective guard in high-strength, wear-resistant steel	●
Rear plates adjustable with Fast Regulation spring dampers	●

TRACTOR EQUIPMENT REQUIRED

- Variable speed gearbox
- Hydraulic valves: 2–6
- Front ballast if necessary

» Accessories on p. 30

Images for illustrative purposes only. The product may vary due to design modifications.