

PT-PREDATOR

STONE CRUSHER



SKF Equipped

HARDOX IN MY BODY

MODEL	3200	3500	3700
Power required HP	200-260	210-260	220-260
Power required kW	147-191	154-191	162-191
Working width mm	3214	3465	3714
Total width mm	3464	3715	3964
Bits* n°	213	235	249
Rotor rpm	253	253	253
Weight** kg	3550	3950	4150

*Net of additional bits for rotor balancing **Approximate

EQUIPMENT	STANDARD
3 points universal hitch (Category 3)	●
Front oscillating bar hitch	●
Single speed unit, 1000 rpm	●
Size 503 reinforced rotor with Ø 25 high-strength, wear-resistant steel bits	●
Oil-bath idler-side support	●
Protective rings for the transmission support and the idler-side support	●
Fixed central PTO shaft (tractor side fork 1” 3/4 Z20)	●
Side PTO shaft with cam system	●
Hydraulic opening and closing of the units with 4 cylinders and controlled locking valves	●
Side gear transmission in oil bath with oversized gears	●
Bearing support with special seals, Labyrinth Bearing Protection by Valentini	●
Rear containment plates and adjustable crushed product screening grids with mechanical jack	●
Counter protective guard in high-strength, wear-resistant steel	●
Rear plates adjustable with Fast Regulation spring dampers	●

TRACTOR EQUIPMENT REQUIRED
- Variable speed gearbox
- Hydraulic valves: 2–4
- Front ballast if necessary

» Accessories on p. 30

Images for illustrative purposes only. The product may vary due to design modifications.