FR - RAMBO-S2



140-230 HP

15-25 cm

20 cm

SKF Equipped

HARDOX IN MY BODY

MODEL	1800	2000	2300
Power required HP	140-230	150-230	160-230
Power required kW	103-169	110-169	118-169
Working width mm	1825	2075	2325
Total width mm	2175	2425	2675
Bits* n°	154	170	188
Rotor rpm	259	259	259
Weight** kg	2920	3200	3350

*Net of additional bits for rotor balancing **Approximate

EQUIPMENT	STANDARD
3 points universal hitch (Category 2 and 3)	●
Single speed unit, 1000 rpm	●
Ø 636 reinforced rotor with Ø 25 high-strength, wear-resistant steel bits	●
Protective rings for the transmission support	●
Central PTO shaft with shear bolt (tractor side fork 1” 3/8 Z6)	●
Double side gear transmission in oil bath by Valentini 4G	●
Bearing support with special seals, Labyrinth Bearing Protection by Valentini	●
Rear containment plates and adjustable screening grids for crushed material with hydraulic jacks	●
Adjustable front conveyors with hydraulic jacks	●
Adjustable skids with hydraulic jacks	●
Protective shroud casing and sledge on outer side	●
Counter protective guard in high-strength, wear-resistant steel	●
Friction timing system by Valentini	●

TRACTOR EQUIPMENT REQUIRED
- Variable speed gearbox
- Hydraulic valves: 2–4
- Front ballast if necessary

» Accessories on p. 30

Images for illustrative purposes only. The product may vary due to design modifications.