110-150 Hp

15-25 cm

20 cm

AP - APACHE



SKF Equipped

HARDOX IN MY BODY

MODEL	1000	1300	1500
Power required HP	110-150	120-150	130-150
Power required kW	81-110	89-110	96-110
Working width mm	1075	1325	1575
Total width mm	1460	1710	1960
Teeth* n°	36	46	56
Rotor rpm	266	266	266
Weight** kg	1580	1670	1850

*Net of additional bits for rotor balancing **Approximate

EQUIPMENT	STANDARD
3 points universal hitch (Category 2 and 3)	●
Single speed unit, 540 rpm	●
Ø 635 reinforced rotor with size 40 cutting teeth in high-strength, wear-resistant steel	●
Protective rings for the transmission support and the idler-side support	●
Central PTO shaft with shear bolt (tractor side fork 1” 3/8 Z6)	●
Single side gear transmission in oil bath by Valentini 4G	●
Oil-bath idler-side support	●
Bearing support with special seals, Labyrinth Bearing Protection by Valentini	●
Lamiere posteriori di contenimento regolabili con martinetto meccanico	●
Adjustable front conveyors with mechanical jacks	●
Working depth skids adjustable with a mechanical jack	●
Protective shroud casing and sledge on outer side	●
Counter protective guard in high-strength, wear-resistant steel	●
Friction timing system by Valentini	●

TRACTOR EQUIPMENT REQUIRED
- Variable speed gearbox
- Hydraulic valves: 2–4
- Front ballast if necessary

» Accessories on p. 44

Images for illustrative purposes only. The product may vary due to design modifications.