AU - AURORA DT

200-400 HP

28 cm



STONE BURIER

SKF Equipped

MODEL	3000	3500	4000
Power required HP	200-400	230-400	280-400
Power required kW	147-294	169-294	206-294
Working width mm	3100	3600	4100
Total footprint mm	3500	4000	4500
Hoes n°	72	84	96
Hoes rotor/blades-points rpm	245 / 306	245 / 306	245 / 306
Weight* W/ CAGE ROLLER Ø575 kg	2480	2800	3200

*Approximate

EQUIPMENT	STANDARD
3 points universal hitch (Category 3N)	●
Single speed unit, 1000 rpm	●
Ø 600 reinforced rotor with high-strength, wear-resistant steel flanges	●
Helical blades: 6 per flange, size 90×10 mm	●
External scraper blades	●
Central PTO shaft with shear bolt (tractor side fork 1" 3/4 Z20)	●
Double side transmission with gears in oil bath by Valentini 4G	●
Spherical roller bearing	●
Bearing support with special seals, Labyrinth Bearing Protection by Valentini	●
Reinforced top link brackets	●
Adjustable rear sheets with Fast Regulation shock absorbers	●
Spring rear grid	●
ROLLER V. 2 mechanical jacks for depth adjustment	●
ROLLER V. Roller differs from the machine outline	●
ROLLER V. Protective shroud casing and sledge on outer side	●

- For tough or stony soils, it is recommended to fit the rotary tiller with counter flanges
- For better soil refinement, it is recommended to install ridging shares or side discs

» Accessories on p. 56
» Rollers on p. 58

Images for illustrative purposes only. The product may vary due to design modifications.