FG - FIGHTER

130-220 HP

28 cm



SKF Equipped

MODEL	3700	4200	4700
Power required HP	130-220	140-220	160-220
Power required kW	96-162	103-162	118-162
Working width mm	3750	4250	4750
Total footprint mm	4000	4500	5000
Hoes n°	84	96	108
Hoes rotor/blades-points rpm	229 / 289	229 / 289	229 / 289
Weight* W/ CAGE ROLLER Ø475 kg	2800	3030	3330

*Approximate

EQUIPMENT		STANDARD
3 points universal hitch (Category 3)		●
Front oscillating bar hitch		●
Front fixed bar attachment ready for quick coupler		●
Central anchor		●
Single speed unit, 1000 rpm		●
Ø540 reinforced rotor with high-strength steel flanges		●
Helical blades: 6 per flange, size 80×8 mm		●
Oil-bath non-drive side support		●
External scraper blades		●
Fixed central PTO shaft (tractor side fork 1” 3/8 Z6)		●
Side PTO shaft with shear bolt		●
Side gear transmission with gears in oil bath		●
Ball bearing		●
Bearing support with special seals, Labyrinth Bearing Protection by Valentini		●
Hydraulic opening and closing of the units with 2 cylinders and controlled locking valves		●
Automatic hydraulic device with safety transport hooks		●
Adjustable rear sheets with Fast Regulation shock absorbers		●
Spring rear grid		●
ROLLER V.	Mod. 3700: 2 mechanical jacks for depth adjustment (1 per roller)	●
	Mod. 4200/4700: 4 mechanical jacks for depth adjustment (2 per roller)	●
	Roller parallel to the transmission	●
	Automatic rear roller alignment device by Valentini – on request	
	Casing protection cap	●

- For tough or stony soils, it is recommended to fit the rotary tiller with counter flanges
- For better soil refinement, it is recommended to install ridging shares or side discs

» Accessories on p. 56
» Rollers on p. 58

Images for illustrative purposes only. The product may vary due to design modifications.