AP - APOLLO BIO

110-190 Hp

1-15 cm



SKF Equipped

MODEL	2500	2800	3000	3300
Power required HP	110-190	120-190	140-190	150-190
Power required kW	81-142	88-142	102-142	110-142
Working width mm	2600	2850	3100	3350
Total footprint mm	2800	3050	3300	3550
Hoes n°	60	66	72	78
Hoes rotor rpm	324	324	324	324
Weight* kg	1350	1460	1610	1690

*Approximate

EQUIPMENT	STANDARD
3 points universal hitch (Category 2 and 3N)	●
Single speed unit, 1000 rpm	●
Ø 540 reinforced rotor with high-strength, wear-resistant steel flanges	●
Square blades: 6 per flange, size 90×10 mm, with counterflanges	●
Oil-bath non-drive side support	●
External scraper blades	●
Central PTO shaft with shear bolt (tractor side fork 1” 3/8 Z6)	●
Single lateral transmission with gears in oil bath by Valentini 4G	●
Spherical roller bearing	●
Bearing support with special seals, Labyrinth Bearing Protection by Valentini	●
BIO model rear plates adjustable by mechanical jack	●
Single front wheels with screw adjustment	●
Rubber guard extensions	●
Hitch extensions	●

» Accessories on p. 30

Images for illustrative purposes only. The product may vary due to design modifications.