MS - MAXI SQUALO BIO



BIO TILLER

SKF Equipped

MODEL	4700	5200	5700	6200
Power required HP	200-340	230-340	250-340	280-340
Power required kW	147-250	170-250	184-250	206-250
Working width mm	4250	4750	5250	5750
Total footprint mm	4500	5000	5500	6000
Hoes n°	96	108	120	132
Hoes rotor rpm	324	324	324	324
Weight* kg	3300	3410	3590	3770

*Approximate

EQUIPMENT	STANDARD
3 points universal hitch (Category 3N)	●
Front oscillating bar hitch	●
Front fixed bar attachment ready for quick coupler	●
Central retractable anchor – BIO model	●
Single speed unit, 1000 rpm	●
Ø 540 reinforced rotor with high-strength, wear-resistant steel flanges	●
Square blades: 6 per flange, size 90×10 mm, with counterflanges	●
Oil-bath non-drive side support	●
External scraper blades	●
Fixed central PTO shaft (tractor side fork 1” 3/4 Z20)	●
Side PTO shaft with disc clutch	●
Hydraulic opening and closing of the units with 4 cylinders and controlled locking valves	●
Double side transmission with gears in oil bath by Valentini 4G	●
Spherical roller bearing	●
Bearing support with special seals, Labyrinth Bearing Protection by Valentini	●
BIO model rear plates adjustable by mechanical jack	●
Front wheels (double pair) with screw adjustment	●
Mechanical locking system for the machine in working position	●
Rubber guard extensions	●

» Accessories on p. 30

Images for illustrative purposes only. The product may vary due to design modifications.