SS - SUPER SQUALO BIO

BIO TILLER

130-290 HP

1-15 cm



SKF Equipped

MODEL	3700	4200	4700	5200
Power required HP	130-290	160-290	190-290	220-290
Power required kW	96-213	118-213	140-213	162-213
Working width mm	3750	4250	4750	5250
Total footprint mm	4000	4500	5000	5500
Hoes n°	84	96	108	120
Hoes rotor rpm	310	310	310	310
Weight* kg	2400	2550	2700	3000

*Approximate

EQUIPMENT	STANDARD
3 points universal hitch (Category 3N)	●
Front oscillating bar hitch	●
Front fixed bar attachment ready for quick coupler	●
Central retractable anchor – BIO model	●
Single speed unit, 1000 rpm	●
Ø 540 reinforced rotor with high-strength, wear-resistant steel flanges	●
Square blades: 6 per flange, size 80×8 mm, with counterflanges	●
Oil-bath non-drive side support	●
External scraper blades	●
Fixed central PTO shaft (tractor side fork 1” 3/8 Z6)	●
Side PTO shaft with shear bolt	●
Hydraulic opening and closing of the units with 4 cylinders and controlled locking valves	●
Double side gear transmission with oversized gears in oil bath	●
Spherical roller bearing	●
Bearing support with special seals, Labyrinth Bearing Protection by Valentini	●
BIO model rear plates adjustable by mechanical jack	●
Front wheels with screw adjustment: single up to model 4700, twin for model 5200	●
Mechanical locking system for the machine in working position	●
Rubber guard extensions	●

» Accessories on p. 30

Images for illustrative purposes only. The product may vary due to design modifications.