UR - URANO BIO



SKF Equipped

MODEL	2300	2500	2800	3000
Power required HP	80-150	90-150	100-150	110-150
Power required kW	58-110	67-110	75-110	79-110
Working width mm	2350	2600	2850	3100
Total footprint mm	2550	2800	3050	3300
Hoes n°	54	60	66	72
Hoes rotor rpm	310	310	310	310
Weight* kg	1190	1280	1390	1560

*Approximate

EQUIPMENT	STANDARD
3 points universal hitch (Category 2 and 3N)	●
Single speed unit, 1000 rpm	●
Ø 540 reinforced rotor with high-strength, wear-resistant steel flanges	●
Square blades: 6 per flange, size 80×8 mm, with counterflanges	●
Oil-bath non-drive side support	●
External scraper blades	●
Central PTO shaft with shear bolt (tractor side fork 1” 3/8 Z6)	●
Single side transmission with oversized gears in oil bath	●
Spherical roller bearing	●
Bearing support with special seals, Labyrinth Bearing Protection by Valentini	●
BIO model rear plates adjustable by mechanical jack	●
Single front wheels with screw adjustment	●
Rubber guard extensions	●
Hitch extensions	●

» Accessories on p. 30

Images for illustrative purposes only. The product may vary due to design modifications.