PO - POSEIDON

150-250 HP

28 cm



SKF Equipped

MODEL	2500	2800	3000	3300
Power required HP	150-250	180-250	200-250	220-250
Power required kW	110-186	132-186	147-186	161-186
Working width mm	2600	2850	3100	3350
Total footprint mm	2800	3050	3300	3550
Hoes n°	60	66	72	78
Hoes rotor/blades-points rpm	245 / 306	245 / 306	245 / 306	245 / 306
Weight* W/ CAGE ROLLER Ø600 kg	1780	1940	2100	2280

*Approximate

EQUIPMENT	STANDARD
3 points universal hitch (Category 3N)	●
Single speed unit, 1000 rpm	●
Ø 600 reinforced rotor with high-strength, wear-resistant steel flanges	●
Helical blades: 6 per flange, size 90×10 mm	●
Oil-bath non-drive side support	●
External scraper blades	●
Central PTO shaft with shear bolt (tractor side fork 1" 3/4 Z20)	●
Single lateral transmission with gears in oil bath by Valentini 4G	●
Spherical roller bearing	●
Bearing support with special seals, Labyrinth Bearing Protection by Valentini	●
Top link brackets	●
Adjustable rear sheets with Fast Regulation shock absorbers	●
ROLLER V. 2 mechanical jacks for depth adjustment	●
Roller differs from the machine outline	●
Protective shroud casing and sledge on outer side	●

Images for illustrative purposes only. The product may vary due to design modifications.

- For tough or stony soils, it is recommended to fit the rotary tiller with counter flanges

» Equipment on p. 21 » Rollers on p. 58