SS - SUPER SQUALO

130-290 HP

28 cm



SKF Equipped

MODEL	3700	4200	4700	5200
Power required HP	130-290	160-290	190-290	220-290
Power required kW	96-213	118-213	140-213	162-213
Working width mm	3750	4250	4750	5250
Total footprint mm	4000	4500	5000	5500
Hoes n°	84	96	108	120
Hoes rotor/blades-points rpm	253 / 310	253 / 310	253 / 310	253 / 310
Weight* W/ CAGE ROLLER Ø510 kg	2400	2550	2700	3000

*Approximate

EQUIPMENT		STANDARD
	3 points universal hitch (Category 3N)	●
	Front oscillating bar hitch	●
	Front fixed bar attachment ready for quick coupler	●
	Central anchor	●
	Single speed unit, 1000 rpm	●
	Ø 540 reinforced rotor with high-strength, wear-resistant steel flanges	●
	Helical blades: 6 per flange, size 80×8 mm	●
	Oil-bath non-drive side support	●
	External scraper blades	●
	Fixed central PTO shaft (tractor side fork 1” 3/8 Z6)	●
	Side PTO shaft with shear bolt	●
	Hydraulic opening and closing of the units with 4 cylinders and controlled locking valves	●
	Automatic hydraulic device with safety transport hooks	●
	Double side gear transmission with oversized gears in oil bath	●
	Spherical roller bearing	●
	Bearing support with special seals, Labyrinth Bearing Protection by Valentini	●
	Adjustable rear sheets with Fast Regulation shock absorbers	●
ROLLER V.	Mod. 3700: 2 mechanical jacks for depth adjustment (1 per roller)	●
ROLLER V.	Mod. 4200/4700/5200: 4 mechanical jacks for depth adjustment (2 per roller)	●
ROLLER V.	Roller parallel to the transmission	●
ROLLER V.	Automatic rear roller alignment device by Valentini – on request	
ROLLER V.	Casing protection cap	●

- For tough or stony soils, it is recommended to fit the rotary tiller with counter flanges

» Equipment on p. 21 » Rollers on p. 58

Images for illustrative purposes only. The product may vary due to design modifications.