UR - URANO



SKF Equipped

MODEL	2300	2500	2800	3000
Power required HP	80-150	90-150	100-150	110-150
Power required kW	58-110	67-110	75-110	79-110
Working width mm	2350	2600	2850	3100
Total footprint mm	2550	2800	3050	3300
Hoes n°	54	60	66	72
Hoes rotor/blades-points rpm	253 / 310	253 / 310	253 / 310	253 / 310
Weight* w/ CAGE ROLLER Ø410 kg	1250	1350	1480	1600

*Approximate

EQUIPMENT		STANDARD
3 points universal hitch (Category 2 and 3N)		●
Single speed unit, 1000 rpm		●
Ø 540 reinforced rotor with high-strength, wear-resistant steel flanges		●
Helical blades: 6 per flange, size 80×8 mm		●
Oil-bath non-drive side support		●
External scraper blades		●
Central PTO shaft with shear bolt (tractor side fork 1” 3/8 Z6)		●
Single side transmission with oversized gears in oil bath		●
Spherical roller bearing		●
Bearing support with special seals, Labyrinth Bearing Protection by Valentini		●
Top link brackets for model 2500		●
Adjustable rear sheets with Fast Regulation shock absorbers		●
ROLLER V.	Mod. 2300/2500: 1 mechanical jack for depth adjustment	●
	Mod. 2800/3000: 2 mechanical jacks for depth adjustment	●
	Roller differs from the machine outline	●
	Protective shroud casing and sledge on outer side	●

- For tough or stony soils, it is recommended to fit the rotary tiller with counter flanges

» Equipment on p. 21 » Rollers on p. 58

Images for illustrative purposes only. The product may vary due to design modifications.