ZE - ZEUS

220-400 HP

28 cm



SKF Equipped

MODEL	3000	3300	3500	3800	4000
Power required HP	200-400	220-400	230-400	250-400	280-400
Power required kW	147-296	161-296	169-296	184-296	206-296
Working width mm	3100	3350	3600	3900	4100
Total footprint mm	3500	3750	4000	4300	4500
Hoes n°	72	78	84	90	96
Hoes rotor/blades-points rpm	245 / 306	245 / 306	245 / 306	245 / 306	245 / 306
Weight* w/ CAGE ROLLER Ø600 kg	2155	2328	2502	2676	2850

*Approximate

EQUIPMENT	STANDARD
3 points universal hitch (Category 3N)	●
Single speed unit, 1000 rpm	●
Ø 600 reinforced rotor with high-strength, wear-resistant steel flanges	●
Helical blades: 6 per flange, size 90×10 mm	●
Oil-bath non-drive side support	●
External scraper blades	●
Central PTO shaft with shear bolt (tractor side fork 1” 3/4 Z20)	●
Single lateral transmission with gears in oil bath by Valentini 4G	●
Spherical roller bearing	●
Bearing support with special seals, Labyrinth Bearing Protection by Valentini	●
Top link brackets	●
Adjustable rear sheets with Fast Regulation shock absorbers	●
ROLLER V. 2 mechanical jacks for depth adjustment	●
Roller differs from the machine outline	●
Casing protection cap	●

- For tough or stony soils, it is recommended to fit the rotary tiller with counter flanges

» Equipment on p. 21 » Rollers on p. 58

Images for illustrative purposes only. The product may vary due to design modifications.