RA-C 550-700

270-450 HP

55-70 cm



SKF Equipped

HARDOX IN MY BODY

MODEL	550×500	550×600	700×700	700×800
Power required HP	300-400	270-300	400-450	400-450
Power required kW	220-296	200-221	296-333	296-333
Working width mm	500	600	700	800
Total width mm	2100	1870	2100	2100
Working depth* cm	55	55	70	70
Rotor rpm	168	168	168	168
Transmissions n°	2	1	2	2
Weight* kg	6100	5600	6800	7200

*Approximate

EQUIPMENT	STANDARD
3 points universal hitch (Category 3 e 4L N)	●
Single speed unit, 1000 rpm with free wheel	●
Mod. 550×500/600: Ø 1670 rotor with Ø 35 high-strength, wear-resistant steel bits	●
Mod. 700×700/800: Ø 1870 rotor with Ø 35 high-strength, wear-resistant steel bits	●
Protective rings for the transmission support	●
Central PTO shaft with shear bolt (tractor side fork 1" 3/4 Z20)	●
Mod. 550X600: Single side gear transmission in oil bath by Valentini	●
Mod. 550X500 and 700X700/800: Double side gear transmission in oil bath by Valentini	●
Bearing support with special seals, Labyrinth Bearing Protection by Valentini	●
Protective hood in high-strength, wear-resistant steel	●

TRACTOR EQUIPMENT REQUIRED

- Variable speed gearbox
- Hydraulic valves: 2–4
- Front ballast if necessary

» Accessories on p. 30

Images for illustrative purposes only. The product may vary due to design modifications.