RA-L 700-1000

130-220 HP

70-100 cm



SKF Equipped

HARDOX IN MY BODY

MODEL	700×200	700×300	800×200	800×300	900×200	900×300	1000×200	1000×300
Power required HP	130-180	130-180	140-180	140-180	150-200	150-200	170-220	170-220
Power required kW	96-134	96-134	103-134	103-134	112-149	112-149	127-164	127-164
Working width mm	220	300	220	300	220	300	220	300
Total width mm	2070	2070	2070	2070	2070	2070	2070	2070
Working depth** cm	70	70	80	80	90	90	100	100
Rotor rpm	171	171	171	171	215	215	215	215
Bits* n°	60	105	60	105	85	120	85	120
Weight** kg	3440	3640	3440	3640	4050	4200	4050	4200

*Net of additional bits for rotor balancing **Approximate

EQUIPMENT	STANDARD
3 points universal hitch (Category 2)	●
Single speed unit, 540 rpm	●
Reinforced rotor with high-strength, wear-resistant steel bits	●
Oil-bath idler-side support	●
Protective rings for the transmission support	●
Central PTO shaft with shear bolt	●
Single side gear transmission in oil bath by Valentini	●
Bearing support with special seals, Labyrinth Bearing Protection by Valentini	●
Protective hood in high-strength, wear-resistant steel	●
Mechanical adjustment skid kit	●
Mod. 400×100/400×150/500×150: Fixed side discharge chute	●
Mod. 500×300/600×200: Conveyor belt	●

TRACTOR EQUIPMENT REQUIRED
- Variable speed gearbox
- Hydraulic valves: 2–4
- Front ballast if necessary

» Accessories on p. 30

Images for illustrative purposes only. The product may vary due to design modifications.