RA 1200-1500

280-450 HP

115-145 cm

TRENCH WHEEL



SKF Equipped

HARDOX IN MY BODY

MODEL	1200×400	1500×400	1500×500
Power required HP	280-320	350-400	380-450
Power required kW	208-237	259-296	281-333
Working width mm	400	400	500
Total width mm	2300	2300	2300
Working depth** cm	115	145	145
Bits* n°	148	100-76***	150-98***
Bits Ø mm	25	35	35
Rotor rpm	152	152	152
Weight** kg	6700	7900	8500

*Net of additional bits for rotor balancing **Approximate ***The value varies depending on the rotor design

EQUIPMENT	STANDARD
3 points universal hitch (Category 3 up to mod. 1200×400, 4L N from mod. 1500×400)	●
Single speed unit, 1000 rpm	●
Mod. 1200: Ø 2100 rotor with Ø 25 high-strength, wear-resistant steel bits	●
Mod. 1500: Ø 2400 rotor with Ø 35 high-strength, wear-resistant steel bits	●
Protective rings for the transmission support	●
Central PTO shaft with cam-type torque limiter (tractor side fork 1" 3/4 Z20)	●
Single side gear transmission in oil bath by Valentini 4G	●
Bearing support with special seals, Labyrinth Bearing Protection by Valentini	●
Protective hood in high-strength, wear-resistant steel	●

TRACTOR EQUIPMENT REQUIRED
- Variable speed gearbox
- Hydraulic valves: 2–4
- Front ballast if necessary

» Accessories on p. 30

Images for illustrative purposes only. The product may vary due to design modifications.