


# GORILLA




| MODEL | 2200 | 2400 |
|---|---|---|
| Potenza HP | 200-300 | 200-300 |
| Potenza kW | 147-220 | 147-220 |
| Working width mm | 2200 | 2400 |
| Total width mm | 2600 | 2800 |
| Teeth* n° | 51 | 57 |
| Flow rate l/min | 300-400 | 300-400 |
| Max. operating pressure bar | 380 | 380 |
| Weight** kg | 2350 | 2570 |

*Net of additional bits for rotor balancing **Approximate

| EQUIPMENT | STANDARD |
|---|---|
| Universal quick hitch | ● |
| Adjustable side support skids with Hardox® wear plate | ● |
| Hydraulically opening front door | ● |
| Electro-hydraulic kit for front door hydraulic control | ● |
| Manually adjustable mechanical push bar | ● |
| Rotor with reversible double-insert tools | ● |
| Double transmission with 5+5 belts | ● |
| Two fixed displacement 108 cc piston hydraulic motors | ● |
| 3-function valve: anti-shock, anti-cavitation, flow rate limiter | ● |
| Nitrogen accumulator with shock-absorbing function for pressure spikes | ● |
| Pressure gauge for monitoring pressure during mulcher operation | ● |

**CARRIER MACHINE EQUIPMENT**
- Hydraulic valves: 2–6

Images for illustrative purposes only. The product may vary due to design modifications.