50-80 HP

70-100 l/min

280 bar max.

15 cm

PICCHIO



MODEL	1300	1600
Potenza HP	50-65	65-80
Potenza kW	37-49	49-60
Working width mm	1300	1500
Total width mm	1520	1720
Teeth* n°	26	30
Flow rate l/min	70-100	70-100
Max. operating pressure bar	280	280
Weight** kg	620	690

*Net of additional bits for rotor balancing **Approximate

EQUIPMENT	STANDARD
Bobcat universal mounting plate	●
Rear chains and rubber flaps	●
Without front door	●
Mechanical push bar	●
DCR rotor with reversible fixed tools with double carbide insert	●
DCR Bite Limiter system with Hardox® 450 wear-resistant profiles	●
Internal counter-blades inside the housing for very fine material shredding	●
Single transmission with 3 belts	●
Piston hydraulic motor available in 34 cc or 47 cc displacement	●
3-function valve: anti-shock, anti-cavitation, flow rate limiter	●
2 m hydraulic hoses with flat-face quick couplings	●
Nitrogen accumulator with shock-absorbing function for pressure spikes	●

CARRIER MACHINE EQUIPMENT
- Hydraulic valves: 2–6

Images for illustrative purposes only. The product may vary due to design modifications.