

PT-PREDATOR

HP 200/260 - kW 147/191



EQUIPAGGIAMENTO STANDARD:

- Attacco universale a 3 punti (3^a cat.)
- Attacco barre anteriori oscillanti
- Gruppo monovelocità 1000 giri/min
- Rotore rinforzato Ø503 con picchi
- Rotore con picchi Ø 25 in "ACCIAIO ALTO RESISTENZIALE e ANTIUSURA"
- Supporto lato folle a bagno d'olio
- Anelli di protezione supporto trasmissione e supporto lato folle
- Cardano centrale fisso (forcella lato trattore 1" 3/4 Z20)
- Cardano laterale a camme
- Apertura e chiusura idraulica dei corpi con 4 martinetti e valvole di blocco controllate
- Trasmissione laterale ad ingranaggi "MAGGIORATI" in bagno d'olio
- Supporti cuscinetto con tenute speciali "Labyrinth Bearing Protection by Valentini"
- Lamiere posteriori di contenimento e griglie di selezione del prodotto frantumato, regolabili con martinetto meccanico
- Contro cofano di protezione in "ACCIAIO ALTO RESISTENZIALE e ANTIUSURA"
- Lamiere posteriori regolabili con ammortizzatori a molla "Fast Regulation"

Note equipaggiamento trattori

- Cambio vario
- Distributori idraulici richiesti da 2 a 4
- Se necessario, dotare il trattore di zavorra anteriore

STANDARD EQUIPMENT:

- 3 point universal hitch (Category 3)
- Front oscillating bar hitch
- Single speed unit, 1000 rpm
- Reinforced rotor, Ø 503 with bits
- Rotor with Ø 25 bits in "HIGH-RESISTANCE AND WEAR RESISTANT STEEL"
- Idle side support in oil bath
- Transmission support and idle side support protection rings
- Central fixed cardan (tractor side fork 1 3/4" Z20)
- Side cardan with cam clutch
- Hydraulic opening and closing of the bodies with 4 jacks and controlled block valves
- Lateral transmission with "OVERSIZE" gears in oil bath
- Bearing support with special seals, "Labyrinth Bearing Protection by Valentini"
- Rear containment sheets and selection grids for crushed product that can be adjusted with a mechanical jack
- Protective counter bonnet in "HIGH-RESISTANCE AND WEAR RESISTANT STEEL"
- Adjustable rear sheets with "Fast Regulation" shock absorbers

Tractor equipment notes

- Variable transmission
- Hydraulic distributors requested from 2 to 4
- If necessary, equip the tractor front ballast



T7 1:2,58_SJ

MODELLO	POTENZA		LARGHEZZA LAVORO	INGOMBRO TOTALE	PICCHI**	PROFONDITA' DI LAVORO* SU BANCO DI ROCCIA	PROFONDITA' DI LAVORO* TERRENO MOSSO	ROTORE	PESO* RULLO PACKER Ø 500
MODEL	POWER		WORKING WIDTH	TOTAL FOOTPRINT	BITS**	WORKING DEPTH* ON ROCK BANK	WORKING DEPTH* SOFT GROUND	ROTOR	WEIGHT* PACKER ROLLER Ø 500
	HP	KW	mm	mm	n° - No.	cm	cm	giri/min - rpm	Kg
3200	200/260	147/191	3214	3464	213	7	15	253	3550
3500	210/260	154/191	3465	3715	235	7	15	253	3950
3700	220/260	162/191	3714	3964	249	7	15	253	4150

* Approssimativo
* Approximate weight

** Al netto dei denti aggiunti per bilanciare il rotore
** Net additional teeth to balance the rotor